

STORAGE TANK FLOATING FILTERS AND HOSES

FUNCTION: The floating filter is used to extract and filter rainwater out of the storage tank, cistern, pond or well.



Fig. RH9532C
 Coarse Filter Housing with 1200 micron Mesh and 1 1/4" (32) Connection (WISY SZ9928)



Fig. RH9532F
 Fine Filter Housing with 300 micron Mesh and 1 1/4" (32) Connection (WISY SZ9936)



Fig. RH9532C-2
 Coarse Filter Housing with 1200 micron Mesh and 2" (51) Connection (WISY SZ9991)



Fig. RH9532F-2
 Fine Filter Housing with 300 micron Mesh and 2" (51)" Connection (WISY SZ9931)



A product of WISY AG in cooperation with RMS.

REGULARLY FURNISHED:
 Stainless Steel Floating Filter, Polyethylene Float Ball, 7' Long Connection Hose Suitable for Suction or Submersible Pumps.

NOTE: Longer hoses are available through your local representative.

NOTE: Dimensions shown in parentheses are in millimeters.

DRAWING NUMBER
 sRH9532

SIZE
A

SCALE:
 NONE

DATE:
 09/21/07

APPROVED BY:
 TWK

CHECKED BY:
 TWK

DRAWN BY:
 JJ

RH9532

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

FIGURE NUMBER

REV.	DATE	DESCRIPTION	BY	CKD. BY
A	02/02/09	Revised Text	JJ	TWK

WEIGHT POUNDS	VOLUME CUBIC FEET

FIGURE NUMBER
RH9532